




扩展型接口 Interface extension



- 可拆装、安装简易（即插即用）
- 经产品的设置菜单可轻松配置
- 3路接口, 配有
 - **Ethernet (LAN)**
 - **USB**
 - **Analog**
- 与下列产品系列兼容
 - **EA-PSI 9000 T**
 - **EA-EL 9000 T**
 - **EA-PS 9000 T**

- **Retrofittable, simple installation (plug 'n play)**
- **Easy configuration via a setup menu on the device**
- **3-way interface with**
 - **Ethernet (LAN)**
 - **USB**
 - **Analog**
- **Compatible to series**
 - **EA-PSI 9000 T**
 - **EA-EL 9000 T**
 - **EA-PS 9000 T**

可选接口模块IF-KE4, 通过三路接口可扩展EA-EL 9000 T, EA-PS 9000 T和EA-PSI 9000 T系列产品的标准USB端口。

它提供两个数字接口端口, 以太网/ LAN和USB, 以及一个Sub-D 15针模拟接口连接器。这些接口可使产品适应和连接到模拟与数字控制应用, 作为选择。

技术规格:

- 尺寸(宽x高x深) : 76 x 30 x 95 mm
- 总重: 200 g
- 连接器:
 - 1x RJ 45 (LAN)
 - 1x USB-B类
 - 1x Sub-D 15针
- 与产品隔离耐压最大为1500 V DC
- 订购编号: 33 100 231

The optionally available and retrofittable interface module IF-KE4 extends the standard USB port featured in the series EA-EL 9000 T, EA-PS 9000 T and EA-PSI 9000 T by a three-way interface front.

It offers two digital interface ports, Ethernet/LAN and USB, as well as an analog interface connector as Sub-D 15-pole version. These interfaces can be used to adapt and connect the devices to a choice of analog and digital control applications.

Technical specifications:

- Dimensions (WxHxD): 76 x 30 x 95 mm
- Total weight: 200 g
- Connectors:
 - 1x RJ 45 (LAN)
 - 1x USB type B
 - 1x Sub-D 15-pole
- Galvanic isolation to the device: max. 1500 V DC
- Ordering number: 33 100 231